

35 t. Teleskop Autokran 35 GMT - AT

Tragfähigkeit [t]
 (nach DIN 15019.2)
 abgestützt , 360° Arbeitsbereich

Ausladung (m)	Auslegerlanger [m]					abgestützt
	9,80	14,47	19,13	23,80	30,8	
3,0	35,00					
3,5	30,00					
4,0	27,00	22,00				
4,5	25,00	20,00				
5,0	22,50	18,35	16,60			
6,0	19,00	15,50	13,00	10,00		
7,0	16,35	13,45	11,00	9,10		
8,0	14,00	11,65	10,20	8,80	7,10	
9,0		10,00	9,10	7,40	6,00	
10,0		8,50	8,00	6,80	5,10	
11,0		7,25	7,10	6,00	5,00	
12,0		6,25	6,10	5,80	4,80	
13,0			5,30	5,00	4,00	
14,0			4,80	4,80	3,80	
15,0			4,00	4,50	3,50	
16,0			3,80	3,45	3,00	
17,0			3,00	3,00	2,80	
18,0				2,65	2,50	
19,0				2,30	2,40	
20,0				2,00	2,30	
21,0				1,75	2,15	
22,0					2,00	
23,0					1,80	
24,0					1,60	
25,0					1,45	
26,0					1,30	
27,0					1,15	
28,0					1,00	
29,0						